

## RIB 713 - Specificații tehnice



### Descriere

RIB 713 este o anvelopă cu bandă de oțel pentru utilaje agricole. Ca răspuns la creșterea gradului de conștientizare a compactării scăzute a solului în agricultura modernă, RIB 713 a fost proiectată cu tehnologia IF. Acest lucru îi permite anvelopei să suporte sarcini mai grele la presiuni de umflare mai mici și oferă o amprentă mai mare cu o distribuție uniformă a greutateii. Structura cu bandă din oțel oferă o rezistență excelentă la perforare și, prin urmare, o protecție sporită împotriva pătrunderii cioturilor și a deteriorării relative, chiar dacă intră pe miriște. În plus, clasa de viteză "D" (65 km/h - 40 mph) permite transferuri rapide pe drum. RIB 713 este contribuția BKT pentru a maximiza atât productivitatea, cât și eficiența activității dvs. agricole.

### UM

US Standard

### Construcție

 RADIAL

### Mașinării

Agricultură: Mașini de implementare

Versiune	STUBBLE RESISTANT
Tip	TL
Dimensiunea anvelopei	IF 280/70 R 15
LI/SS	128 D

## Dimensiuni US Standard

Usa code	94046201
Lățimea secțiunii (inch)	11
Overall Diameter (inch)	30.7
Static Loaded Radius (inch)	13.7
Rolling Circumference (inch)	92.8
Rim Rec	W 8
ECE	E4-106R-001820
TRA Code	I1

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35	41	46	52
From 5 to 40 mph	1480	1710	1950	2230	2470	2700	2940	3140	3460	3740	3970

Imprimat pe 4/25/2024 10:43 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..