

RIB 774 (A) - Specificații tehnice



Descriere

RIB 774 (A) este o anvelopă pentru utilaje cu secțiune joasă, care oferă o capacitate mare de încărcare și un ciclu de viață lung. Este potrivită pentru recoltarea fânului și aplicații de transport cu prese de balotat și remorci.

UM

Standard internațional

Construcție

 BIAS

Mașinării

Agricultură: Presă de balotat • Mașină de recoltare a fânului • Remorcă

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	200/60 - 14.5
LI/SS FREE ROLLING	113 A8

Dimensiuni Standard internațional

Rating de sarcină	14
Lățimea secțiunii (mm)	210
Overall Diameter (mm)	610
Static Loaded Radius (mm)	288
Rolling Circumference (mm)	1888
Rim Rec	AG 6.75
ECE	E11-106R-003608

Load capacity (Kg)

km/h / bar	7.00
10 FR	1610
25 FR	1370
30 FR	1290
40 FR	1150

Imprimat pe 4/23/2024 1:04 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..