

RIB 774 (C) - Specificații tehnice



Descriere

RIB 774 (C) este o anvelopă pentru utilaje cu secțiune joasă și lățime îngustă. Este ideală pentru recoltarea fânului și aplicațiile de transport cu prese de balotat și remorci, atât pe drum, cât și în condiții off-road. Are o capacitate mare de încărcare și un ciclu lung de viață al anvelopei.

UM

US Standard

Construcție

 BIAS

Mașinării

Agricultură: Presă de balotat • Mașină de recoltare a fânului • Remorcă

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	19.0/45 - 17
LI/SS FREE ROLLING	138 A8

Dimensiuni US Standard

Usa code	94027330
Rating de sarcină	10
Lățimea secțiunii (inch)	17.9
Overall Diameter (inch)	33.3
Static Loaded Radius (inch)	15.2
Rolling Circumference (inch)	99.1
Rim Rec	16.00
ECE	E11-106R-004589

Load capacity (lbs)

mph / psi	33
5 FR	7290
15 FR	6190
20 FR	5830
25 FR	5200

Imprimat pe 4/23/2024 3:16 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..