

RIB 774 (C) - Specificații tehnice



Descriere

RIB 774 (C) este o anvelopă pentru utilaje cu secțiune joasă și lățime îngustă. Este ideală pentru recoltarea fânului și aplicațiile de transport cu prese de balotat și remorci, atât pe drum, cât și în condiții off-road. Are o capacitate mare de încărcare și un ciclu lung de viață al anvelopei.

UM

US Standard

Construcție

 BIAS

Mașinării

Agricultură: Presă de balotat • Mașină de recoltare a fânului • Remorcă

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	215/75 - 17.5
LI/SS FREE ROLLING	134 A8

Dimensiuni US Standard

Usa code	94011001
Rating de sarcină	12
Lățimea secțiunii (inch)	8.7
Overall Diameter (inch)	30.5
Static Loaded Radius (inch)	14.2
Rolling Circumference (inch)	90.9
Rim Rec	6.75
ECE	E11-106R-004590

Load capacity (lbs)

mph / psi	100
5 FR	6550
15 FR	5570
20 FR	5240
25 FR	4670

Imprimat pe 4/23/2024 10:43 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..