

RIB 900 - Specificații tehnice



Descriere

RIB 900 este potrivită pentru transport, cultivarea solului și recoltarea fânului cu remorci, utilaje și prese de balotat. Oferă o capacitate mare de încărcare și un ciclu lung de viață al anvelopei.

UM

Standard internațional

Construcție

 BIAS

Mașinării

Agricultură: Presă de balotat • Mașină de recoltare a fânului • Mașini de implementare • Remorcă

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	400/60 - 15.5
LI/SS FREE ROLLING	139 A8

Dimensiuni Standard internațional

Rating de sarcină	10
Lățimea secțiunii (mm)	405
Overall Diameter (mm)	875
Static Loaded Radius (mm)	380
Rolling Circumference (mm)	2564
Rim Rec	AG 13.00

Load capacity (Kg)

km/h / bar	2.50
10 FR	3135
25 FR	2665
30 FR	2510
40 FR	2240

Imprimat pe 4/28/2024 10:29 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..