

## RIB IMPLEMENT (B) - Specificații tehnice



### Descriere

UTENSUL RIB (B) a fost special concepută pentru utilaje agricole. Această anvelopă ideală pentru agricultura modernă este fabricată dintr-un compus rezistent la mișcări, care oferă o protecție excelentă la perforare. RIB IMPLEMENT (B) este o anvelopă cu model de benzi de rulare cu 5 nervuri, cu o carcasă puternică pentru o durată de viață mai lungă. Este alegerea potrivită pentru toate condițiile de operare, care necesită o capacitate mare de încărcare împreună cu rezistență scăzută la rulare. &nbsp;

### UM

Standard internațional

### Construcție

 BIAS

### Mașinării

Agricultură: Mașini de implementare

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	49 - 17
LI/SS DRIVE WHEEL	146 A8/143 B
LI/SS FREE ROLLING	158 A8/154 B

## Dimensiuni Standard internațional

Rating de sarcină	20
Lățimea secțiunii (mm)	425
Overall Diameter (mm)	1200
Rim Rec	13.0
Rim Alt	14.0
ECE	E11-106R-004653

## Load capacity (Kg)

km/h / bar	4.0
40 FR	4250
50 FR	3750
40 DW	3000
50 DW	2725

Imprimat pe 4/19/2024 10:09 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..