

RIB IMPLEMENT (B) - Specificații tehnice



Descriere

UTENSUL RIB (B) a fost special concepută pentru utilaje agricole. Această anvelopă ideală pentru agricultura modernă este fabricată dintr-un compus rezistent la mișcări, care oferă o protecție excelentă la perforare. RIB IMPLEMENT (B) este o anvelopă cu model de benzi de rulare cu 5 nervuri, cu o carcasă puternică pentru o durată de viață mai lungă. Este alegerea potrivită pentru toate condițiile de operare, care necesită o capacitate mare de încărcare împreună cu rezistență scăzută la rulare.

UM

US Standard

Construcție

 BIAS

Mașinării

Agricultură: Mașini de implementare

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	49 - 17
LI/SS DRIVE WHEEL	146 A8/143 B
LI/SS FREE ROLLING	158 A8/154 B

Dimensiuni US Standard

Usa code	94046591
Rating de sarcină	20
Lățimea secțiunii (inch)	16.7
Overall Diameter (inch)	47.2
Rim Rec	13.0
Rim Alt	14.0
ECE	E11-106R-004653

Load capacity (lbs)

mph / psi	58
25 FR	9370
30 FR	8270
25 DW	6610
30 DW	6000

Imprimat pe 4/19/2024 4:49 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..