

Dimensiuni Standard internațional

TKPH	1
Lățimea secțiunii (mm)	645
Overall Diameter (mm)	1811
Static Loaded Radius (mm)	823
Rolling Circumference (mm)	5514
SRI (mm)	875
Rim Rec	DW 20 B
Rim Alt	DW 18 L
ECE	E11-106R-004078

Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2
65	2820	3480	4080	4740	5340	6000
50	3045	3760	4405	5120	5765	6480
40	3245	4000	4690	5450	6140	6900
30	3385	4175	4895	5690	6410	7200

Imprimat pe 4/27/2024 12:15 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..