

## RIDEMAX IT 697 (M+S) - Specificații tehnice



### Descriere

RIDEMAX IT 697 M+S reprezintă cel mai bun răspuns la nevoile antreprenorilor moderni din agricultură în sezonul de iarnă. Este perfectă pentru aplicații de transport și la nivel de municipalitate. Această anvelopă de iarnă pentru tractoare asigură o aderență extraordinară pentru toate operațiunile pe drumuri înghețate și înzăpezite fără a fi necesară montarea lanțurilor de zăpadă. Datorită canelurilor benzii de rulare și carcasei puternice, un tractor poate fi condus în deplină stabilitate, chiar și la viteze mari. Designul benzii de rulare a fost dezvoltat special pentru condiții grele și asigură o rezistență scăzută la rulare, care oferă economie de combustibil plus stabilitate mare.

### UM

US Standard

### Construcție

 RADIAL

### Mașinării

Agricultură: Tractor

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	650/65 R 38 IND
LI/SS	170 D/175 A8

## Dimensiuni US Standard

Usa code	94055418
TMPH	1
Lățimea secțiunii (inch)	25.4
Overall Diameter (inch)	71.3
Static Loaded Radius (inch)	32.4
Rolling Circumference (inch)	217.1
Rim Rec	DW 20 B
Rim Alt	DW 18 L
ECE	E11-106R-004078

## Load capacity (lbs)

mph / psi	17	23	29	35	41	46
40	6220	7670	8990	10450	11770	13230
30	6710	8290	9710	11290	12710	14290
25	7150	8820	10340	12010	13540	15210
20	7460	9200	10790	12540	14130	15870

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 5/11/2025 11:43 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..