RM 500 - Specificații tehnice

Descriere

RM 500 este o anvelopă radială cu benzi din oțel, potrivită pentru aplicațiile cu utilaje de recoltat. Are o carcasă puternică și un design special al benzii de rulare care oferă o capacitate mare de încărcare și o rezistență deosebită la tăiere și așchiere. Datorită amprentei sale mari, RM 500 asigură o distribuție excelentă a presiunii pe sol cu o compactare redusă a solului, pe lângă tracțiune excelentă.

UM

US Standard

Construcție

RADIAL

Mașinării

Agricultură: Mașină de recoltare

Versiune	STEEL BELTED
Tip	TL
Dimensiunea anvelopei	500/80 R 28
LI/SS	176 A8 / 164 A8
LI/SS DRIVE WHEEL	164 A8
LI/SS FREE ROLLING	176 A8

Dimensiuni US Standard

Usa code	94063697
Lățimea secțiunii (inch)	19.8
Overall Diameter (inch)	58.9
Static Loaded Radius (inch)	25
Rolling Circumference (inch)	171.5
Rim Rec	W 16 L
Rim Alt	W 15 L
ECE	E11-106R-005990

Load capacity (lbs)

mph / psi	12	15	17	23	29	35	41	46
25 Free Rolling	6110	7040	7830	9710	11120	12840	14560	15650
25 Drive Wheel	4300	4960	5510	6830	7830	9040	10250	11020

Imprimat pe 4/24/2024 10:37 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..