



ROCK GRIP L4 - Specificații tehnice



Descriere

ROCK GRIP (L-4) este o anvelopă cu straturi înclinate concepută pentru operațiunile cu încărcătorul frontal în condiții dificile de încărcare și pe teren accidentat. Compusul său special conceput, rezistent la tăiere și la aşchieri, reduce la minimum perforațiile, reducând astfel timpul de nefuncționare a mașinii. Adâncimea benzii de rulare (L-4) asigură un ciclu de viață extins al anvelopei.

UM

Standard internațional

Construcție

❖ BIAS

Mașinării

Industrial: Buldozer • Încărcător

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	14.00 - 25

Dimensiuni Standard internațional

Rating de sarcină	32
Overall Width (mm)	375
Overall Diameter (mm)	1410
Static Loaded Radius (mm)	649
Rolling Circumference (mm)	4173
Rim Rec	10.00/1.5
TRA Code	L4

Load capacity (Kg)

km/h / bar	10.00
10	10500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 5/11/2025 10:24 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..