

ROCK GRIP (T) - Specificații tehnice



Descriere

ROCK GRIP (E-4) se potrivește cel mai bine camioanelor de încărcare/descărcare din cariere și aplicații miniere pe distanțe scurte pentru a transporta sarcini grele. Compusul special al benzii de rulare minimizează tăieturile și perforările pe cele mai dificile terenuri. ROCK GRIP (E-4) oferă o tracțiune excepțională și un ciclu de viață extins al anvelopei.

UM

US Standard

Construcție

 BIAS

Mașinării

OTR: Camion On/Off • Autobasculantă rigidă

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	10.00 - 20

Dimensiuni US Standard

Usa code	94050802
Rating de sarcină	18
Overall Width (inch)	11
Overall Diameter (inch)	42.9
Rim Rec	7.5
Rim Alt	7.0

Load capacity (lbs)

mph / psi	110
55 LS/LD	6170

Imprimat pe 4/26/2024 6:50 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..