

## RT 857 - Specificații tehnice



### Descriere

RT 857 este o anvelopă concepută pentru aplicații de cultivare a solului. Carcasa puternică oferă durabilitate și tracțiune excelente. Compusul benzii de rulare rezistent la miriște are o rezistență ridicată la tăiere și așchiere.

### UM

Standard internațional

### Construcție

 RADIAL

### Mașinării

Agricultură: Tractor

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	320/85 R 24 (12.4 R 24)
LI/SS	122 A8/B

## Dimensiuni Standard internațional

Lățimea secțiunii (mm)	329
Overall Diameter (mm)	1154
Static Loaded Radius (mm)	528
Rolling Circumference (mm)	3449
SRI (mm)	550
Rim Rec	W 11
Rim Alt	W 10 ; W 9
ECE	E11-106R-002976
TRA Code	R1

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	825	960	1095	1230	1365	1500
40	825	960	1095	1230	1365	1500
30	885	1030	1175	1320	1465	1605
10 LT	1110	1290	1470	1650	1830	2010
10 HT	885	1030	1175	1320	1465	1605

Imprimat pe 4/18/2024 3:59 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..