

## RT 857 - Specificații tehnice



### Descriere

RT 857 este o anvelopă concepută pentru aplicații de cultivare a solului. Carcasa puternică oferă durabilitate și trașiune excelente. Compusul benzii de rulare rezistent la mișcări are o rezistență ridicată la tăiere și aşchieri.

### UM

US Standard

### Construcție

 RADIAL

### Mașinării

Agricultură: Tractor

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	320/85 R 28 (12.4 R 28)
LI/SS	124 A8/B

## Dimensiuni US Standard

Usa code	94041923
Lățimea secțiunii (inch)	13
Overall Diameter (inch)	49.4
Static Loaded Radius (inch)	22.7
Rolling Circumference (inch)	148.8
Rim Rec	W 11
Rim Alt	W 9 ; W 10
ECE	E4-106R-000757
TRA Code	R1

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	1940	2260	2580	2900	3220	3530
25	1940	2260	2580	2900	3220	3530
20	2080	2420	2770	3110	3450	3780
5 LT	2600	3030	3460	3880	4310	4730
5 HT	2080	2420	2770	3110	3450	3780

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 5/11/2025 5:26 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..