

RT 857 - Specificații tehnice



Descriere

RT 857 este o anvelopă concepută pentru aplicații de cultivare a solului. Carcasa puternică oferă durabilitate și tracțiune excelente. Compusul benzii de rulare rezistent la miriște are o rezistență ridicată la tăiere și așchiere.

UM

Standard internațional

Construcție

RADIAL

Mașinării

Agricultură: Tractor

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	340/85 R 28 (13.6 R 28)
LI/SS	127 A8/B

Dimensiuni Standard internațional

Lățimea secțiunii (mm)	353
Overall Diameter (mm)	1289
Static Loaded Radius (mm)	599
Rolling Circumference (mm)	3908
SRI (mm)	625
Rim Rec	W 12
Rim Alt	W 11
ECE	E4-106R-000759
TRA Code	R1

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	965	1120	1280	1435	1595	1750
40	965	1120	1280	1435	1595	1750
30	1035	1200	1370	1540	1710	1875
10 LT	1290	1505	1715	1925	2135	2345
10 HT	1035	1200	1370	1540	1710	1875

Imprimat pe 4/18/2024 4:02 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..