

SIERRA MAX - Specificații tehnice



Descriere

SIERRA MAX este anvelopa BKT potrivită pentru orice tip de teren, cât și pentru gazon și grădină. Construcția sa radială oferă o deplasare semnificativ mai lină și mai confortabilă pe terenuri extreme, cum ar fi deșerturi sau suprafețe noroioase și stâncoase. Designul special al benzii de rulare împreună cu amprenta sa mai lată oferă o tracțiune remarcabilă înainte și laterală.

UM

Standard internațional

Construcție

 RADIAL

Mașinării

Agricultură: ATV

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	AT 25 X 8 R 12
LI/SS	43 N

Dimensiuni Standard internațional

Lățimea secțiunii (mm)	206
Overall Diameter (mm)	640
Static Loaded Radius (mm)	292
Rolling Circumference (mm)	1899
Rim Rec	6.5
Star Rating	***
ECE	E11-75R-005088

Load capacity (Kg)

km/h / bar	0.50
140	155

Imprimat pe 4/20/2024 12:28 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..