

## SKID POWER ( CHEVRON ) - Specificații tehnice



### Descriere

SKID POWER (CHEVRON) a fost special concepută pentru mini-încărcătoare în aplicații de construcții. Are o tracțiune excelentă, precum și proprietăți îmbunătățite de auto-curățare. SKID POWER (CHEVRON) este potrivită în special pentru suprafețe instabile și prezintă o rezistență ridicată la tăiere și așchiere. &nbsp; &nbsp;

### UM

US Standard

### Construcție

 BIAS

### Mașinării

Industrial: Mini-încărcător

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	7.00 - 15

## Dimensiuni US Standard

Usa code	94017171
Rating de sarcină	6
Lățimea secțiunii (inch)	8
Overall Diameter (inch)	30
Static Loaded Radius (inch)	13.7
Rolling Circumference (inch)	90.4
Rim Rec	5.50 F
Rim Alt	6 LB

## Load capacity (lbs)

mph / psi	60
5	3180
10	2510

Imprimat pe 4/23/2024 3:26 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..