

SKID POWER HD (A) - Specificații tehnice



Descriere

SKID POWER HD (A) a fost proiectată pentru mini-încărcătoare în aplicații de construcții. Anvelopa dispune de o bandă de rulare cu adâncime suplimentară și o protecție suplimentară a pereților laterali pentru o rezistență excelentă la tăiere și așchiere și durabilitate excepțională. SKID POWER HD (A) este anvelopa ideală pentru suprafețe instabile și lucrări grele.

UM

US Standard

Construcție

 BIAS

Mașinării

Industrial: Mini-încărcător

Versiune	IMPLEMENT
Tip	TL
Dimensiunea anvelopei	260/70 - 16.5 (10 - 16.5)
LI/SS	120 A8

Dimensiuni US Standard

Usa code	94052219
Rating de sarcină	10
Lățimea secțiunii (inch)	10.5
Overall Diameter (inch)	30.5
Static Loaded Radius (inch)	14
Rolling Circumference (inch)	90.4
Rim Rec	8.25
ECE	E4-106R-002338

Load capacity (lbs)

mph / psi	75
25	3085

Imprimat pe 4/25/2024 4:19 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..