



## SKID POWER SK - Specificații tehnice



## Descrivere

SKID POWER SK a fost special concepută pentru mini-  
încărcătoare în aplicații de construcții. Apărătorile sale  
laterale și de protecție a jantei, precum și banda de rulare  
adâncă asigură un ciclu de viață extins al anvelopei.     

UM

Standard international

## Construcție



## Maşinării

Industrial: Mini-încărcător

|                       |           |
|-----------------------|-----------|
| Versiune              | IMPLEMENT |
| Tip                   | TL        |
| Dimensiunea anvelopei | 12 - 16.5 |
| LI/SS                 | 125 A8    |

## Dimensiuni Standard internațional

|                            |                 |
|----------------------------|-----------------|
| Rating de sarcină          | 10              |
| Lățimea secțiunii (mm)     | 312             |
| Overall Diameter (mm)      | 825             |
| Static Loaded Radius (mm)  | 375             |
| Rolling Circumference (mm) | 2434            |
| Rim Rec                    | 9.75            |
| ECE                        | E11-106R-003545 |

## Load capacity (Kg)

|            |      |
|------------|------|
| km/h / bar | 4.50 |
| 40         | 1650 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 6/1/2025 11:22 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..