

SKID POWER - Specificații tehnice



Descriere

SKID POWER a fost proiectată pentru mini-încărcătoare în aplicații de construcții. Prezintă o tracțiune excelentă, precum și caracteristici îmbunătățite de auto-curățare. Anvelopa are o bandă de rulare foarte adâncă, împreună cu o protecție suplimentară pe laterală, oferind o rezistență excelentă la tăiere și așchiere și o durabilitate remarcabilă. SKID POWER este anvelopa ideală pentru suprafețe instabile.

UM

Standard internațional

Construcție

 BIAS

Mașinării

Industrial: Mini-încărcător

Versiune	IMPLEMENT
Tip	TL
Dimensiunea anvelopei	12 - 16.5
LI/SS	125 A8

Dimensiuni Standard internațional

Rating de sarcină	10
Lățimea secțiunii (mm)	305
Overall Diameter (mm)	821
Static Loaded Radius (mm)	373
Rolling Circumference (mm)	2422
Rim Rec	9.75
ECE	E11-106R-003535

Load capacity (Kg)

km/h / bar	4.50
40	1650

Imprimat pe 4/19/2024 4:45 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..