

SKID POWER - Specificații tehnice



Descriere

SKID POWER a fost proiectată pentru mini-încărcătoare în aplicații de construcții. Prezintă o tracțiune excelentă, precum și caracteristici îmbunătățite de auto-curățare. Anvelopa are o bandă de rulare foarte adâncă, împreună cu o protecție suplimentară pe laterală, oferind o rezistență excelentă la tăiere și așchiere și o durabilitate remarcabilă. SKID POWER este anvelopa ideală pentru suprafețe instabile.

UM

US Standard

Construcție

 BIAS

Mașinării

Industrial: Mini-încărcător

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	14 - 17.5

Dimensiuni US Standard

Usa code	94017164
Rating de sarcină	14
Lățimea secțiunii (inch)	14
Overall Diameter (inch)	37
Static Loaded Radius (inch)	16.7
Rolling Circumference (inch)	109.2
Rim Rec	10.5

Load capacity (lbs)

mph / psi	80
5	8540
10	6750
15	6240

Imprimat pe 4/16/2024 12:17 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..