

## SM 53 - Specificații tehnice



### Descriere

SM 53 a fost special proiectată pentru încărcătoare în minieră subterană și aplicații de încărcare. Are stabilitate ridicată, precum și un design neted al benzii de rulare, oferind o rezistență excelentă la tăiere. &nbsp;

### UM

Standard internațional

### Construcție

 BIAS

### Mașinării

OTR: Vehicul pentru exploatare minieră subterană

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	9.00 - 20

## Dimensiuni Standard internațional

Rating de sarcină	16
Overall Width (mm)	266
Overall Diameter (mm)	1040
Static Loaded Radius (mm)	472
Rolling Circumference (mm)	3080
Rim Rec	7.0
TRA Code	L3S
Tread Depth	23

## Load capacity (Kg)

	km/h / bar	7.25
	10	3965
	15	3450
	25	3170

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 3/26/2025 10:56 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..