

SM 53 - Specificații tehnice



Descriere

SM 53 a fost special proiectată pentru încărcătoare în minieră subterană și aplicații de încărcare. Are stabilitate ridicată, precum și un design neted al benzii de rulare, oferind o rezistență excelentă la tăiere.

UM

US Standard

Construcție

 BIAS

Mașinării

OTR: Vehicul pentru exploatare minieră subterană

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	9.00 - 20

Dimensiuni US Standard

Usa code	94041510
Rating de sarcină	16
Overall Width (inch)	10.5
Overall Diameter (inch)	40.9
Static Loaded Radius (inch)	18.6
Rolling Circumference (inch)	121.3
Rim Rec	7.0
TRA Code	L3S
Tread Depth	29

Load capacity (lbs)

mph / psi	105
5	8740
10	7610
15	6990

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 3/26/2025 10:49 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..