

SM 55 L5S - Specificații tehnice



Descriere

SM 55 (L-5S) este o anvelopă cu straturi diagonale, ideală pentru operațiunile miniere subterane. Compusul special conceput al benzii de rulare rezistent la tăiere și aşchiere reduce la minimum perforațiile, reducând astfel timpul de nefuncționare a mașinii. Adâncimea foarte adâncă a benzii de rulare L-5 S garantează o durată de viață prelungită a anvelopei. Anvelopa este disponibilă și într-o versiune cu bandă din oțel.

UM

US Standard

Construcție

 BIAS

Mașinării

OTR: Autobasculantă cu profil redus (LPDT) • Vehicul pentru exploatare minieră subterană

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	7.00 - 12

Dimensiuni US Standard

Usa code	94044986
Rating de sarcină	14
Overall Width (inch)	8.1
Overall Diameter (inch)	28
Static Loaded Radius (inch)	12.7
Rolling Circumference (inch)	85
Rim Rec	5.00 S
TRA Code	L5S
Tread Depth	39

Load capacity (lbs)

mph / psi	131
15	4670

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 6/1/2025 7:02 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..