

SNOW - RIDE (A) - Specificații tehnice



Descriere

SNOW-RIDE este în special potrivită pentru aplicații municipale și de întreținere în condiții de iarnă, cu încărcătoare compacte și mini-încărcătoare. Are o tracțiune excelentă și este ideală pentru operațiuni pe gheață și zăpadă. Modelul său special conceput elimină riscurile de alunecare și asigură un ciclu de viață mai lung al anvelopei.

UM

Standard internațional

Construcție

 BIAS

Mașinării

Agricultură: Încărcător compact
Industrial: Mini-încărcător

| | |
|-----------------------|--------------|
| Versiune | STANDARD |
| Tip | TL |
| Dimensiunea anvelopei | 17.5/65 - 20 |

Dimensiuni Standard internațional

| | |
|----------------------------|--------|
| Rating de sarcină | 10 |
| Lățimea secțiunii (mm) | 445 |
| Overall Diameter (mm) | 1095 |
| Static Loaded Radius (mm) | 493 |
| Rolling Circumference (mm) | 3285 |
| Rim Rec | W 14 L |

Load capacity (Kg)

| km/h / bar | 2.40 |
|------------|------|
| 10 | 3195 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 11/11/2024 8:33 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..