

## SNOW - RIDE (B) - Specificații tehnice

### Descriere

SNOW-RIDE este potrivită în special pentru aplicații rutiere în condiții de iarnă, cu mini-încărcătoare. Are o tracțiune excelentă și este ideală pentru operațiuni pe gheață și zăpadă. Modelul său special conceput elimină riscurile de alunecare.

### UM

Standard internațional

### Construcție

 BIAS

### Mașinării

Industrial: Buldozer • Încărcător



Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	17.5 - 25

## Dimensiuni Standard internațional

Rating de sarcină	12
Lățimea secțiunii (mm)	445
Overall Diameter (mm)	1348
Static Loaded Radius (mm)	608
Rolling Circumference (mm)	4044
Rim Rec	14.00/1.5
TRA Code	L2

## Load capacity (Kg)

km/h / bar	3.50
10	6150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 2/14/2025 3:23 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..