

## SUPER SAND - Specificații tehnice



### Descriere

SUPER SAND este potrivită în special pentru remorci care operează pe suprafețe nisipoase în condiții de vreme caldă. Are o capacitate mare de flotație și este ideală pentru toate operațiunile care necesită un nivel ridicat de manipulare. &nbsp;

### UM

US Standard

### Construcție

 BIAS

### Mașinării

Industrial: Remorcă

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	14.00 - 20

## Dimensiuni US Standard

Usa code	94025558
Rating de sarcină	12
Lățimea secțiunii (inch)	15.2
Overall Diameter (inch)	48.2
Rim Rec	10.00 V
Rim Alt	10.00 W

## Load capacity (lbs)

	mph / psi	35
40 LS		5205
40 LD		4540

Imprimat pe 4/25/2024 10:55 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..