

## SUPER TRAX HD - Specificații tehnice



### Descriere

SUPER TRAX HD a fost special proiectată pentru stivuitoare în operațiuni grele de manipulare a materialelor, inclusiv aplicații portuare și miniere. Banda de rulare foarte adâncă este realizată dintr-un compus unic rezistent la uzură, care asigură o durată de viață mai lungă. SUPER TRAX HD are o carcasă puternică și un perete lateral ranforsat, rezultând atât stabilitate excelentă, cât și manevrare superioară în modul de ridicare. Apărătoarea special concepută pentru jantă oferă protecție împotriva penelor și a deteriorării roților în zona flanșei jantei.

### UM

US Standard

### Construcție

 BIAS

### Mașinării

Industrial: Stivuitoare

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	6.00 - 9

## Dimensiuni US Standard

Usa code	94055449
Rating de sarcină	12
Lățimea secțiunii (inch)	6.6
Overall Diameter (inch)	21.6
Static Loaded Radius (inch)	10.1
Rolling Circumference (inch)	65.8
Rim Rec	4.00 E

## Load capacity (lbs)

mph / psi	145
15 LOAD WHEEL	4155
15 STEER WHEEL	3195
5 OTHER VEHICLES	4155
15 OTHER VEHICLES	3195
STATIC SIDE LOADER	4830

Imprimat pe 4/26/2024 4:49 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..