

TR 117 - Specificații tehnice



Descriere

TR 117 este ideală pentru aplicații de irigare cu irigatoare pivot. Modelul său special conceput oferă tracțiune excelentă și proprietăți de auto-curățare remarcabile.

UM

Standard internațional

Construcție

 BIAS

Mașinării

Agricultură: Instalații de irigare tip pivot

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	11.2 - 24
LI/SS	101 A6

Dimensiuni Standard internațional

Rating de sarcină	4
Lățimea secțiunii (mm)	284
Overall Diameter (mm)	1090
Static Loaded Radius (mm)	509
Rolling Circumference (mm)	3205
Rim Rec	W 10
Rim Alt	W 9
ECE	E4-106R-001966
TRA Code	R1

Load capacity (Kg)

km/h / bar	1.20	1.55
30	825	---
CREEP	---	1585

* - CREEP SPEED - 200 FT/30 MIN (61 M/30 MIN)

Imprimat pe 4/26/2024 10:59 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..