

TR 126 - Specificații tehnice



Descriere

TR 126 este proiectată pentru a se potrivi cu tractoare mici în operațiunile de cultivare a solului. Canelurile adânci și modelul benzii de rulare oferă o tracțiune excelentă și caracteristici remarcabile de capacitate de încărcare, oferind cea mai bună performanță a anvelopei în toate condițiile de operare.

UM

Standard internațional

Construcție

❖ BIAS

Mașinării

Agricultură: Tractor mic

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	7 - 14
LI/SS	72 A6

Dimensiuni Standard internațional

Rating de sarcină	4
Lățimea secțiunii (mm)	170
Overall Diameter (mm)	690
Static Loaded Radius (mm)	320
Rolling Circumference (mm)	2070
Rim Rec	5 JA ; 5 KB
ECE	E11-106R-003356
TRA Code	R1

Load capacity (Kg)

km/h / bar	1.60
30	355

Imprimat pe 4/23/2024 8:21 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..