

## TR 126 - Specificații tehnice



### Descriere

TR 126 este proiectată pentru a se potrivi cu tractoare mici în operațiunile de cultivare a solului. Canelurile adânci și modelul benzii de rulare oferă o tracțiune excelentă și caracteristici remarcabile de capacitate de încărcare, oferind cea mai bună performanță a anvelopei în toate condițiile de operare. &nbsp; &nbsp;

### UM

US Standard

### Construcție

 BIAS

### Mașinării

Agricultură: Tractor mic

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	7 - 14
LI/SS	92 A8

## Dimensiuni US Standard

Usa code	94052639
Rating de sarcină	8
Lățimea secțiunii (inch)	6.7
Overall Diameter (inch)	27.2
Static Loaded Radius (inch)	12.6
Rolling Circumference (inch)	81.5
Rim Rec	5 JA ; 5 KB
ECE	E11-106R-005233
TRA Code	R1

## Load capacity (lbs)

mph / psi	58
25	1390

Imprimat pe 4/23/2024 2:40 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..