

TR 128 - Specificații tehnice



Descriere

TR 128 a fost special concepută pentru tractoare utilitare și motocultoare. Designul lat și adânc și compusul special de rezistență la tăiere și așchiere asigură o durată de viață extinsă a anvelopei. TR 128 oferă tracțiune maximă pe sol umed.

UM

US Standard

Construcție

 BIAS

Mașinării

Agricultură: Timon • Vehicul universal

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	180/85 D 12
LI/SS	63 A6

Dimensiuni US Standard

Usa code	94058129
Rating de sarcină	4
Lățimea secțiunii (inch)	6.5
Overall Diameter (inch)	24.1
Static Loaded Radius (inch)	11.6
Rolling Circumference (inch)	72.7
Rim Rec	5 JA
ECE	E11-106R-004821

Load capacity (lbs)

mph / psi	23
20	600

Imprimat pe 4/19/2024 3:50 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..