TR 135 - Specificații tehnice

Descriere

TR 135 este anvelopa cea mai potrivită pentru tractoare în aplicații de cultivare a solului. Carcasa sa întărită și compusul special de rezistență la tăiere și așchiere asigură un ciclu de viață extins al anvelopei. Tracțiunea, proprietățile de auto-curățare și capacitatea de încărcare sunt caracteristici cheie care fac din anvelopa TR 135 partenerul ideal chiar și în cele mai dificile condiții de teren.

UM

Standard internațional

Construcție

BIAS

Mașinării

Agricultură: Tractor
Industrial: Remorcă

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	11.2 - 20
LI/SS	111 A6

Dimensiuni Standard internațional

Rating de sarcină	8
Lățimea secțiunii (mm)	292
Overall Diameter (mm)	1020
Static Loaded Radius (mm)	466
Rolling Circumference (mm)	3077
Rim Rec	W 10
Rim Alt	W 9 ; 9
ECE	E11-106R-003480
TRA Code	R1

Load capacity (Kg)

km/h / bar	2.40
30	1090

Imprimat pe 4/23/2024 5:45 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..