TR 136 - Specificații tehnice

Descriere

TR 136 a fost dezvoltată de BKT pentru a echipa tractoare și remorci în operațiunile de cultivare a solului și de transport. Această anvelopă oferă o tracțiune îmbunătățită în toate condițiile de lucru, împreună cu cea mai bună rezistență la tăiere și așchiere, pentru a reduce timpul de nefuncționare a mașinii și a crește productivitatea. Datorită numărului crescut de caneluri, TR 136 oferă o tracțiune remarcabilă chiar și la sarcini mari.

UM

Standard internațional

Construcție

BIAS

Mașinării

Agricultură: Tractor • Remorcă

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	16.9 - 30 (14 - 30)
LI/SS	146 A6

Dimensiuni Standard internațional

Rating de sarcină	14
Lățimea secțiunii (mm)	429
Overall Diameter (mm)	1485
Static Loaded Radius (mm)	677
Rolling Circumference (mm)	4455
SRI (mm)	700
Rim Rec	W 15 L
Rim Alt	W 14 L
ECE	E11-106R-005243
TRA Code	R1

Load capacity (Kg)

km/h / bar	2.80
30	3000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 10/12/2024 8:46 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..