

TR 137 - Specificații tehnice



Descriere

TR 137 este cea mai potrivită anvelopă BKT pentru toate operațiunile de recoltare. Asigură o tracțiune excelentă pe câmp chiar și cu sarcini mari. Anvelopa este disponibilă în diferite versiuni: versiunea cu "bandă din aramidă" oferă o mai bună rezistență la perforare și protecție împotriva tuturor deteriorărilor tipice ale acestei aplicații; versiunea "HD" oferă o rezistență extraordinară la tăiere și așchiere și un ciclu de viață extins al anvelopei.

UM

US Standard

Construcție

 BIAS

Mașinării

Agricultură: Mașină de recoltare

Versiune	HD
Tip	TL
Dimensiunea anvelopei	30.5L - 32
LI/SS	167 A8

Dimensiuni US Standard

Usa code	94004355
Rating de sarcină	18
Lățimea secțiunii (inch)	30.3
Overall Diameter (inch)	73.4
Static Loaded Radius (inch)	32.7
Rolling Circumference (inch)	217.3
Rim Rec	DH 27 B
Rim Alt	DW 27 B
ECE	E4-106R-002283
TRA Code	R1

Load capacity (lbs)

mph / psi	30
25	12010

Imprimat pe 4/24/2024 11:28 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..