

TR 144 - Specificații tehnice



Descriere

TR 144 este potrivită pentru echiparea tractoarelor mici pentru a fi utilizate în operațiunile de cultivare a solului. TR 144 asigură performanțe remarcabile în toate condițiile de operare care necesită o tracțiune excelentă la sarcini mari. Este disponibilă și într-o variantă "specială" care este cea mai potrivită pentru lucrări în condiții dificile.

UM

Standard internațional

Construcție

 BIAS

Mașinării

Agricultură: Tractor mic

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	8 - 16
LI/SS	91 A6

Dimensiuni Standard internațional

Rating de sarcină	6
Lățimea secțiunii (mm)	200
Overall Diameter (mm)	785
Static Loaded Radius (mm)	358
Rolling Circumference (mm)	2342
Rim Rec	6 L ; 6 LB ; 6.00 F
ECE	E11-106R-003483
TRA Code	R1

Load capacity (Kg)

km/h / bar	1.90
30	615

Imprimat pe 4/19/2024 10:34 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..