

TR 144 - Specificații tehnice



Descriere

TR 144 este potrivită pentru echiparea tractoarelor mici pentru a fi utilizate în operațiunile de cultivare a solului. TR 144 asigură performanțe remarcabile în toate condițiile de operare care necesită o tracțiune excelentă la sarcini mari. Este disponibilă și într-o variantă "specială" care este cea mai potrivită pentru lucrări în condiții dificile.

UM

Standard internațional

Construcție

 BIAS

Mașinării

Agricultură: Tractor mic

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	8 - 18
LI/SS	85 A6

Dimensiuni Standard internațional

Rating de sarcină	4
Lățimea secțiunii (mm)	195
Overall Diameter (mm)	835
Static Loaded Radius (mm)	385
Rolling Circumference (mm)	2509
Rim Rec	W 6
Rim Alt	W 7 ; 5.50 F
ECE	E11-106R-004328
TRA Code	R1

Load capacity (Kg)

km/h / bar	1.20
30	515

Imprimat pe 4/19/2024 5:19 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..