

TR 145 - Specificații tehnice



Descriere

TR 145 a fost special proiectată pentru tractoare mici. Modelul special al benzii de rulare oferă o tracțiune excelentă și proprietăți remarcabile de auto-curățare. Designul cu caneluri late și adânci asigură o durată de viață extinsă a anvelopei. Anvelopa TR 145 are o suprafață mare de contact care oferă un confort excelent la condus și o stabilitate direcțională înaltă.

UM

US Standard

Construcție

 BIAS

Mașinării

Agricultură: Tractor mic

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	160/90 - 12
LI/SS	72 A8

Dimensiuni US Standard

Usa code	94062744
Rating de sarcină	6
Lățimea secțiunii (inch)	6.3
Overall Diameter (inch)	24.8
Static Loaded Radius (inch)	11.6
Rolling Circumference (inch)	77.5
Rim Rec	4.00
ECE	E11-106R-005854
TRA Code	R1

Load capacity (lbs)

mph / psi	36
2	785

Imprimat pe 4/27/2024 7:31 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..