

## TR 171 - Specificații tehnice



### Descriere

TR 171 este o anvelopă cu bandă de rulare adâncă potrivită pentru tractoare în operațiunile de cultivare a solului. Datorită proprietăților sale remarcabile de auto-curățare, este ideală pentru solul umed și ud. Proiectată cu un compus special, TR 171 oferă tracțiune excelentă și durabilitate extraordinară și în cele mai dificile condiții de funcționare.

### UM

US Standard

### Construcție

 BIAS

### Mașinării

Agricultură: Tractor

Versiune	HD
Tip	TT
Dimensiunea anvelopei	13.6 - 26
LI/SS	131 A8

## Dimensiuni US Standard

Usa code	94057979
Rating de sarcină	12
Lățimea secțiunii (inch)	13.4
Overall Diameter (inch)	50
Static Loaded Radius (inch)	23.2
Rolling Circumference (inch)	148.6
Rim Rec	W 12
Rim Alt	W 11
TRA Code	R1W+

## Load capacity (lbs)

mph / psi	50
25	4300

Imprimat pe 5/3/2024 2:01 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..