

TR 173 - Specificații tehnice



Descriere

TR 173 este o anvelopă de tractor potrivită pentru condiții umede și câmpuri de orez. Modelul special al benzii de rulare oferă proprietăți de auto-curățare remarcabile, pe lângă compactarea redusă a solului datorită unei suprafețe mari de contact.

UM

US Standard

Construcție

 BIAS

Mașinării

Agricultură: Tractor

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	12.4 - 24
LI/SS	111 A8

Dimensiuni US Standard

Usa code	94064120
Rating de sarcină	6
Lățimea secțiunii (inch)	12.4
Overall Diameter (inch)	45.7
Static Loaded Radius (inch)	21.3
Rolling Circumference (inch)	138.1
Rim Rec	W 11
Rim Alt	W 9 ; W 10
ECE	E11-106R-004480
TRA Code	R1W

Load capacity (lbs)

mph / psi	24
25	2400

Imprimat pe 4/26/2024 11:53 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..