

## TR 273 - Specificații tehnice



### Descriere

TR 273 este o anvelopă de tractor potrivită pentru cultivarea solului și concepută special pentru a oferi performanțe maxime pe sol umed și ud. În aceste condiții de sol, este necesară o anvelopă care oferă o aderență superioară și proprietăți de auto-curățare îmbunătățite. TR 273 îndeplinește perfect toate aceste caracteristici. &nbsp;

### UM

US Standard

### Construcție

 BIAS

### Mașinării

Agricultură: Tractor

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	23.1 - 30
LI/SS	154 A8

## Dimensiuni US Standard

Usa code	94045693
Rating de sarcină	14
Lățimea secțiunii (inch)	23.2
Overall Diameter (inch)	68.8
Static Loaded Radius (inch)	31.3
Rolling Circumference (inch)	210.9
Rim Rec	DW 20 A ; DW 20 B
ECE	E11-106R-003645
TRA Code	R2

## Load capacity (lbs)

mph / psi	28
25	8270

Imprimat pe 4/26/2024 7:53 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..