

TR 313 - Specificații tehnice



Descriere

TR 313 este o anvelope de gazon și grădină potrivită pentru operațiunile municipale și de cultivare a solului cu utilaje, mașini de săpat șanțuri și mașini de recoltat livezi. Zona mare de contact oferă o aderență excelentă. Anvelopa TR 313 a fost proiectată pentru a asigura un nivel ridicat de stabilitate și în condiții critice de funcționare, împreună cu proprietăți excelente de auto-curățare.

UM

US Standard

Construcție

 BIAS

Mașinării

Agricultură: Mașini de implementare • Mașină de recoltat din livezi • Mașină de săpat șanțuri

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	31 X 15.50 - 15

Dimensiuni US Standard

Usa code	94025589
Rating de sarcină	8
Lățimea secțiunii (inch)	14.6
Overall Diameter (inch)	30.7
Static Loaded Radius (inch)	13.5
Rolling Circumference (inch)	87.9
Rim Rec	13 LB
ECE	E4-106R-002208

Load capacity (lbs)

mph / psi	45
30	2760

Imprimat pe 4/23/2024 2:42 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..