TR 315 - Specificații tehnice

Descriere

TR 315 este potrivită pentru gazon și grădină, cultivarea solului și operațiunile municipale. Este ideală cu mașini de umplere, mașini de săpat șanțuri și mașini de recoltat livezi. Anvelopa TR 315 are o zonă mare de contact care oferă o aderență excelentă, proprietăți excelente de auto-curățare și o stabilitate remarcabilă în orice condiție.

UM

Standard internațional

Construcție

BIAS

Mașinării

Agricultură: Mașini de implementare • Mașină de recoltat din livezi • Mașină de săpat șanțuri

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	26 X 12.00 - 12

Dimensiuni Standard internațional

Rating de sarcină	12
Lățimea secțiunii (mm)	308
Overall Diameter (mm)	655
Static Loaded Radius (mm)	289
Rolling Circumference (mm)	1905
Rim Rec	10½ JA
Rim Alt	8½ JA ; 9½ JA
ECE	E4-106R-002328

Load capacity (Kg)

km/h / bar	4.50
15	1600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 10/12/2024 9:36 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..