

## TR 360 - Specificații tehnice



### Descriere

TR 360 este potrivită pentru utilaje în transportul rutier și off-road, precum și pentru aplicații de gazon și grădină. Designul deosebit al benzii de rulare împreună cu structura carcasei asigură un ciclu lung de viață al anvelopei.

### UM

US Standard

### Construcție

 BIAS

### Mașinării

Agricultură: Mașini de implementare

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	18 X 7 - 8

## Dimensiuni US Standard

Usa code	94013104
Rating de sarcină	6
Lățimea secțiunii (inch)	7.1
Overall Diameter (inch)	18.1
Static Loaded Radius (inch)	8
Rolling Circumference (inch)	52.5
Rim Rec	5.5
ECE	E4-106R-002184

## Load capacity (lbs)

mph / psi	46
10	990

Imprimat pe 4/17/2024 4:24 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..