

## TR 387 - Specificații tehnice



### Descriere

TR 387 este o anvelopă agroindustrială potrivită pentru remorci și compactoare de trestie de zahăr. Are o capacitate mare de încărcare și este disponibilă în diferite versiuni pentru a satisface cerințele specifice ale utilizatorului în ceea ce privește rezistența la tăiere și aşchiere, servicii în condiții dificile și durabilitate. Versiunea "dual bead" este potrivită în special pentru tractoare industriale și operațiuni de transport cu remorci.

### UM

US Standard

### Construcție

 BIAS

### Mașinării

Agricultură: Remorcă  
Industrial: Compactor

Versiune	DUAL BEAD HD
Tip	TL
Dimensiunea anvelopei	23.1 - 26
LI/SS	157 A8

## Dimensiuni US Standard

Usa code	94030682
Rating de sarcină	18
Lățimea secțiunii (inch)	23.3
Overall Diameter (inch)	61.4
Static Loaded Radius (inch)	27.2
Rolling Circumference (inch)	184.6
Rim Rec	DW 20 B
TRA Code	R3

## Load capacity (lbs)

mph / psi	38
25	9090

Imprimat pe 4/25/2024 11:20 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..