

TR 390 IND - Specificații tehnice



Descriere

TR 390 IND este o anvelopă industrială potrivită pentru remorci și compactoare industriale. Are o capacitate mare de încărcare și este disponibilă în diferite versiuni pentru a satisface cerințele specifice ale utilizatorului în ceea ce privește rezistența la tăiere și așchiere, servicii în condiții dificile și durabilitate. Versiunea "dual bead" este potrivită în special pentru tractoare industriale și operațiuni de transport cu remorci.

UM

US Standard

Construcție

 BIAS

Mașinării

Industrial: Compactor • Tractor industrial • Remorcă

Versiune	DUAL BEAD HD
Tip	TL
Dimensiunea anvelopei	28L - 26
LI/SS	168 A8

Dimensiuni US Standard

Usa code	94065349
Rating de sarcină	20
Lățimea secțiunii (inch)	28.1
Overall Diameter (inch)	61.4
Static Loaded Radius (inch)	27.2
Rolling Circumference (inch)	178.9
Rim Rec	DW 25 B
Rim Alt	DW 23 B
TRA Code	R3

Load capacity (lbs)

mph / psi	42
25	12350

Imprimat pe 12/3/2023 7:13 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..