

TR 393 (B) - Fișa de date



Descriere

Anvelopa TR 393 (B) a fost proiectată special pentru semănători, mașini de împrăștiat și utilaje, atât pentru utilizarea pe șosea, cât și în afara acesteia. Designul special al benzii de rulare asigură cele mai bune proprietăți pentru flotație și autocurățare, pe lângă o durată de viață lungă. Datorită suprafeței mari de contact, TR 393 asigură o tracțiune excelentă și minimizează compactarea solului.

UM

US Standard

Construcție

 BIAS

Mașinării

Agricultură: Presă de balotat • Mașini de implementare •
Mașină de împrăștiat

| SIZE | Version | USACode | TRA Code | LI/SS | PR | RIM REC | RIM ALT | SW | OD | Type | ECE |
|-----------------|-------------------|----------|----------|-------|----|---------|---------|------|------|------|-----------------|
| 31 X 13.50 - 15 | STUBBLE RESISTANT | 94070626 | R3 | 124 B | 12 | 10 LB | | 13.8 | 30.6 | TL | E11-106R-008131 |

Imprimat pe 3/4/2024 1:48 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..