

TR 393 - Fișa de date



Descriere

TR 393 a fost special proiectată pentru prese de balotat fân, mașini de împrăștiat agricole și utilaje care circulă pe șosea și în afara drumului. Designul special al benzii de rulare oferă cele mai bune proprietăți de flotație și auto-curățare, pe lângă o durată lungă de viață. Datorită suprafeței mari de contact, TR 393 asigură o tracțiune excelentă și minimizează compactarea solului.

UM

US Standard

Construcție

 BIAS

Mașinării

Agricultură: Presă de balotat • Mașini de implementare •
Mașină de împrăștiat

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type
16.5L - 16.1 SL	STANDARD	94053261	I2	128 B	6	W14C	W14CH	16.5	40.4	18.1	116.8	TL
21.5L - 16.1 SL	STANDARD	94075171	I2	146 B	10	W 18 CH	W 16 CH	21.5	45.4	0	0	TL

Imprimat pe 3/4/2024 12:53 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..