

TR 461 - Specificații tehnice



Descriere

TR 461 este un model BKT potrivit pentru aplicații municipale și de întreținere cu tractoare, precum și pentru operațiunile de încărcare cu manipolatoare telescopice. Protecția peretelui lateral prezintă o rezistență deosebită împotriva tăieturilor și protuberanțelor, oferind o durată de viață mai lungă chiar și pe suprafețe dure, pe lângă o stabilitate excelentă.

UM

US Standard

Construcție

 BIAS

Mașinării

Industrial: Buldoexcavator • Încărcător telescopic • Tractor industrial

| | |
|-----------------------|------------|
| Versiune | STANDARD |
| Tip | TL |
| Dimensiunea anvelopei | 19.5L - 24 |
| LI/SS | 154 A8 |

Dimensiuni US Standard

| | |
|------------------------------|----------|
| Usa code | 94016778 |
| Rating de sarcină | 14 |
| Lățimea secțiunii (inch) | 19.3 |
| Overall Diameter (inch) | 51.6 |
| Static Loaded Radius (inch) | 22.8 |
| Rolling Circumference (inch) | 151.6 |
| Rim Rec | DW 16 L |
| TRA Code | R4 |

Load capacity (lbs)

| | |
|-----------|------|
| mph / psi | 38 |
| 25 | 8270 |

Imprimat pe 4/27/2024 12:42 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..