TR 882 - Specificații tehnice

Descriere

TR 882 este o anvelopă foarte versatilă, potrivită pentru mai multe aplicații și vehicule. A fost proiectată pentru a se potrivi cu mașini de umplere, mașini de recoltat fân/prese de balotat și mașini de trestie de zahăr. Proiectată cu un compus special pentru a reduce daunele, această anvelopă oferă, de asemenea, durabilitate și tracțiune deosebite pe orice tip de teren. TR 882 este, de asemenea, disponibilă în versiunea cu “bandă din aramidă”, “HD” și “specială” pentru a satisface cerințele specifice ale utilizatorului final.

UM

US Standard

Construcție

BIAS

Mașinării

Agricultură: Presă de balotat • Mașină de recoltare a fânului • Mașini de implementare • Remorcă
Industrial: Remorcă

Versiune	ARAMID BELTED HD
Tip	TL
Dimensiunea anvelopei	400/60 - 15.5
LI/SS DRIVE WHEEL	137 A8
LI/SS FREE ROLLING	149 A8

Dimensiuni US Standard

Usa code	94048304
Rating de sarcină	18
Lățimea secțiunii (inch)	15.7
Overall Diameter (inch)	34.4
Static Loaded Radius (inch)	14.9
Rolling Circumference (inch)	102.6
Rim Rec	AG 13.00
ECE	E11-106R-005354

Load capacity (lbs)

mph / psi	65
5 FR	10030
15 FR	8530
20 FR	8020
25 FR	7160
5 DW	7100
15 DW	6030
20 DW	5680
25 DW	5070

Imprimat pe 4/29/2024 3:57 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..